

APT-P6

2-Way 6.5-inch Pendant Loudspeaker

FEATURES

- Celestion 6.5-inch coaxial driver.
- Custom horn flare designed in collaboration with Celestion.
- Lo-Z & 100v/70v operation via multi-tap transformer.
- Optional wall mount bracket to expand versatility.
- Magnetic edge-to-edge grille with removable HH logo.
- Available in Black and White.

APPLICATIONS

- Restaurants
- Bars
- Corporate facilities
- Retail
- Education

DESCRIPTION

The APT-P6 pendant speaker brings decades of British design and engineering expertise to installation audio. Featuring a Celestion 6.5-inch coaxial driver with a 1.5-inch LF voice coil and 1-inch HF voice coil, the APT-P6 delivers crystal-clear, well-balanced sound. Its custom horn flare profile ensures optimised sound dispersion, making it ideal for a wide range of environments.

The APT-P6 offers a sensitivity of 90dB (1W/1M) and a 120W AES power rating, yielding a maximum SPL of 110dB. With a frequency response of 70Hz to 20kHz, the APT-P6 reproduces beautifully balanced audio. For enhanced low-frequency performance, the APT-P6 pairs perfectly with the APT-W8S surface-mount subwoofer.

Available in sleek black or white finishes, the APT-P6's elegant, tapered profile complements modern spaces and is the perfect solution for architecturally challenging environments, such as those with high ceilings or where traditional ceiling speakers aren't an option. A rear dust cover protects the connectors while maintaining the speaker's sophisticated aesthetic.

The APT-P6 is equipped with a built-in multi-tap transformer, suitable for both Lo-Z and 100V/70V applications, easily adjustable via a rotary switch hidden beneath the magnetic edge-to-edge grille. The rear steel mounting point ensures secure suspension via steel wire or surface mount installation via an optional wall-mount bracket.



SPECIFICATIONS

Specifications	
Model	<i>APT-P6</i>
System type	<i>2-Way Coaxial Pendant Loudspeaker</i>
Driver Specifications	<i>Celestion 6.5-inch Coaxial Driver with 1.5-inch LF VC and 1-inch HF VC</i>
100v Power Options	<i>40W, 20W, 10W</i>
70V Power Options	<i>20W, 10W, 5W</i>
Nominal System Impedance	<i>8 Ohms</i>
Power Rating	<i>120W AES, 240W Continuous, 480W Peak</i>
Recommended Amplifier	<i>MZ-140D, MZ-140Q, MZ-280Q</i>
Sensitivity 1W/1m	<i>90dB</i>
Maximum SPL (1m)	<i>110dB SPL, 116dB SPL (Peak)</i>
Frequency Response	<i>70Hz-20kHz</i>
Input / Link Connector	<i>4-pin Euroblock +/- +/-</i>
Dispersion	<i>120°</i>
Enclosure	
Main Construction Material	<i>ABS</i>
Finish	<i>Black/White ABS</i>
Grille	<i>Black/White Fine Mesh Perforated Steel with Powdercoated Finish</i>
Mounting Bracket	<i>Optional wall mounting bracket.</i>
Mounting Suspension Points	<i>Integrated eyelet for suspended mounting via carabiner.</i>
Dimensions	
Outer Diameter	<i>308mm</i>
Max Depth	<i>305mm</i>
Optional Accessories	
	<i>NA</i>

In the interest of continued development, HH reserves the right to amend product specification without prior notification.

